




24-hour operation

TPS-50S

Excellent Compact Pumps
Sea Water Applicable



Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1M	2M	3M	4M	5M			
TPS-50S	1/10	80	20	3/4"	5	40	38	33	20	-	-	4	114 x 114 x 265	2.5

Remarks: Model with "A" is equipped with wide angle float switch.

SMP Series


Swimming Pool & Water Recycling



SMP-10



SMP-20
SMP-30




Model	Power		Outlet		Max Flow(LPM)	LPM Flow @ Head				Max Head(M)	Dimension L x W x H (mm)	Weight Kg	
	HP	W	mm	Inch		3M	6M	9M	12M				
SMP-10	1	750	40	1-1/2"	310	290	240	175	85	-	14	495 x 180 x 295	8.5
SMP-20	2	1500	50	2"	460	450	415	350	250	100	16	700 x 295 x 420	18.5
SMP-30	3	2100	50	2"	520	515	500	460	395	300	20	700 x 295 x 420	24.5



24-hour operation

TPS-200S

Excellent Compact Pumps
Sea Water Applicable




Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1M	2M	3M	4M	5M			
TPS-200S	1/4	200	32	1-1/4"	5	140	135	120	100	80	55	7	168 x 146 x 288	3.6

Remarks: Model with "A" is equipped with wide angle float switch.

SMC Series

Anti-rusty. Circulating pool water




Model	Output		Outlet		Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch		4M	6M	8M	10M	12M			
SMC-05	1/2	400	25	1"	180	145	100	60	5	-	10	288 x 120 x 190	5.5
SMC-10	1	750	40	1-1/2"	320	195	160	110	10	-	10	276 x 153 x 183	6.5
SMC-20	2	1500	50	2"	535	-	450	350	250	160	13	380 x 202 x 226	12.5



24-hour operation

TPV-200S

Dirty Water Usage
Solid Passage 19 mm
Sea Water Applicable




Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1M	2M	3M	4M	5M			
TPV-200S	1/4	200	32	1-1/4"	19	140	135	120	100	80	55	7	168 x 146 x 288	3.6

Remarks: Model with "A" is equipped with wide angle float switch.

SPA Series

Water Recycling



Model	Output		Outlet		Max Flow(LPM)	LPM Flow @ Head				Max Head(M)	Dimension L x W x H (mm)	Weight Kg	
	HP	W	mm	Inch		2M	4M	6M	8M				
SPA-07	3/4	600	40	1-1/2"	270	260	220	165	95	-	10	354 x 182 x 216	9.5
SPA-10	1	750	40	1-1/2"	320	310	275	230	175	115	14	354 x 182 x 216	10.0