





TAS
Non-clogging vortex impeller
Multi function sewage pump
Drain water to the lowest level



Model	Output		Outlet		Pass solid Solid(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			3M	4.5M	6M	7.5M	9M			
TAS-250	1/3	250	40	1.5"	14	250	215	160	105	45	-	9	225 x 145 x 282	6
TAS-400	1/2	400	50	2"	14	300	250	200	145	90	35	10	250 x 165 x 300	8.5
TAS-750	1	750	50	2"	14	360	350	320	275	215	145	12	250 x 165 x 300	9.5




SH-400



Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	W	mm	Inch			1.5M	2M	3M	4M	5M			
SH-400	1/2	400	40	1-1/2"	20	250	235	210	155	100	50	6	218 x 150 x 363	3.6



BAS Series
Non-clog Vortex Impeller
Solids passage 5~15mm




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			2M	4M	6M	8M	10M			
BAS-100	1/6	100	25	1"	7	120	115	70	-	-	-	6	190 x 130 x 280	5
BAS-200	1/5	200	32	1-1/4"	7	140	130	95	35	-	-	7	190 x 130 x 280	6
BAS-300	1/3	300	40	1-1/2"	9	200	190	150	80	-	-	8	200 x 135 x 285	8
BAS-400	1/2	400	50	2"	12	270	250	210	160	95	-	10	236 x 145 x 352	10
BAS-600	3/4	600	50	2"	15	300	280	240	195	135	60	11	276 x 165 x 425	12

Remarks: Model No. ends with "A" is equipped with float switch.



SH-200/300




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4.5M	6M	7.5M			
SH-200	1/4	200	32	1-1/4"	5	140	135	110	65	-	-	6	196 x 196 x 260	5
SH-300	1/3	250	40	1-1/2"	5	200	195	170	130	75	20	8	196 x 196 x 280	5.5

Remarks: Model with "A" is equipped with float switch.



KSV Series
Non-clog Vortex Impeller
Solids passage 5~20mm




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4.5M	6M	7.5M			
KSV-150	1/5	150	40	1-1/2"	5	200	190	150	85	-	-	6	190 x 140 x 360	6
KSV-250	1/3	250	40	1-1/2"	5	240	230	185	130	60	-	7	190 x 140 x 360	8
KSV-400	1/2	400	50	2"	10	300	295	270	220	155	70	9	215 x 155 x 370	12
KSV-550	3/4	550	50	2"	15	330	320	290	250	190	120	10	260 x 160 x 430	13
KSV-750	1	750	80	3"	15	430	420	395	315	150	-	11	260 x 160 x 430	15
KSV-1500	2	1500	80	3"	20	800	795	770	680	550	380	17	270 x 350 x 610	32

Remarks: Model with "A" is equipped with float switch.
Remarks: Model with "V" is equipped with vertical switch.



SH-48/123



Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4.5M	6M	7.5M			
SH-48	1/3	250	32/40	1-1/4"/1-1/2"	7	170	160	120	70	15	-	6.5	222 x 200 x 135	7.2
SH-123	1/2	400	50	2"	10	360	345	300	240	180	100	9	264 x 246 x 165	12.6

Remarks: Model No. ends with "A" is equipped with float switch.