


# BCV Series


2" pass soild outlet  
Non-clogging vortex impeller design



Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4M	5M	6M			
BCV-400(50Hz)	1/2	400	50	2"	50	360	350	275	210	140	70	7	225 x 150 x 400	7.5
BCV-400(60Hz)	1/2	400	50	2"	50	400	395	355	300	220	130	7	225 x 150 x 400	7.5

# BAV Series

Solids Passage 10~35mm  
Non-clogging vortex impeller design




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4.5M	6M	7.5M			
BAV-150	1/3	150	32	1-1/4"	10	160	150	115	60	-	-	6	190 x 130 x 280	7.3
BAV-250	1/3	250	40	1-1/2"	25	200	190	160	120	70	15	8	190 x 130 x 280	7.3
BAV-400	1/2	400	50	2"	30	300	290	270	235	185	125	10	200 x 135 x 285	12
BAV-550	3/4	550	50	2"	35	340	330	305	270	225	170	12	236 x 145 x 352	12

Remarks: Model No. ends with "S" is included with stainless steel strainer for dirty water discharge.  
Remarks: Model No. ends with "A" is equipped with float switch.



# GD/GDH Series


Stainless Steel Motor Housing



Model	Output		Outlet		Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	KW	mm	Inch		5M	10M	15M	20M	25M			
GD-15	1.5	1	32	1-1/4"	180	170	150	105	-	-	20	245 x 200 x 525	30
GD-20	2	1.5	32	1-1/4"	180	175	160	130	80	-	25	245 x 200 x 525	32
GD-30	3	2.2	32	1-1/4"	210	205	195	180	140	55	28	245 x 200 x 575	35
GDH-15	1.5	1	32	1-1/4"	100	98	95	90	80	50	30	240 x 190 x 500	30
GDH-20	2	1.5	32	1-1/4"	160	155	150	140	120	80	30	240 x 190 x 520	32

# GC Series

All cast Iron Grinder Pump



Model	Output		Outlet		Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	KW	mm	Inch		5M	10M	15M	30M	40M			
GC-20	2	1.5	32	1-1/4"	170	165	150	75	-	-	24	240 x 200 x 560	38
GC-30	3	2.2	50	2"	180	175	170	150	95	-	36	240 x 200 x 560	42
GC-50	5	3.7	65	2-1/2"	340	335	325	290	220	50	42	270 x 238 x 830	55
GC-75	7.5	5.5	65	2-1/2"	360	350	340	310	250	150	50	270 x 238 x 830	60