




VH Series

Submersible Pumps for Fountain and High Building Water Supply




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	W	mm	Inch			5M	10M	20M	30M	40M			
VH-400	1/2	400	32	1-1/4"	1.2	110	102	85	38	-	25	350 X 131 X 183	13	
VH-550	3/4	550	32	1-1/4"	1.2	110	105	90	60	22	35	400 X 131 X 183	14	
VH-750	1	750	32	1-1/4"	1.2	110	107	100	82	60	48	425 X 131 X 183	15	
VH-1000	1.2	1000	32	1-1/4"	1.2	110	107	102	88	70	55	450 X 131 X 183	16	



JKCH Series

5" Multi-stage motor-cooling design.




Model	Output		Stages	Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	W		mm	Inch			5M	10M	20M	30M	40M			
JKCH-20	1/2	400	2	32	1-1/4"	1.2	100	87	65	-	-	20	125 x 125 x 430	11.8	
JKCH-30	3/4	600	3	32	1-1/4"	1.2	100	97	90	50	-	30	125 x 125 x 454	12.8	
JKCH-40	1.1	800	4	32	1-1/4"	1.2	100	97	92	65	35	40	125 x 125 x 478	13.8	
JKCH-50	1.5	1100	5	32	1-1/4"	1.2	100	98	93	75	53	28	125 x 125 x 530	14.8	
JKCH-60	1.8	1350	6	32	1-1/4"	1.2	100	98	95	83	65	45	125 x 125 x 554	15.8	

Remarks: Model No. ends with "A" is equipped with float switch.



KSH Series




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension LxWxH(mm)	Weight Kg
	HP	KW	mm	Inch			3M	6M	9M	12M	15M			
KSH-05	1/2	0.4	40	1-1/2"	2	130	120	85	35	-	18	290 x 168 x 422	16	
KSH-10	1	0.75	40	1-1/2"	2.5	200	190	165	120	30	21	283 x 227 x 465	29	
KSH-20	2	1.5	50	2"	5	320	310	280	230	145	25	283 x 227 x 484	32	
KSH-30	3	2.2	50	2"	6.5	450	440	400	335	255	145	30	395 x 250 x 510	42
KSH-50	5	3.7	80	3"	7	640	620	575	520	450	340	35	455 x 290 x 585	50



BAH Series

High head and Non-clogging Pass Solid 8mm 2 Stages




Model	Output		Outlet		Max Flow(LPM)	LPM Flow @ Head				Max Head(M)	Dimension L x W x H (mm)	Weight Kg	
	HP	W	mm	inch		3M	6M	9M	15M				
BAH-400	1/2	400	32	1-1/4"	180	175	160	140	115	75	20	227 x 160 x 370	13
BAH-750	1	750	40	1-1/2"	220	215	200	185	160	130	25	227 x 160 x 390	15



MT Series

Sprinkler Water Supply



Model	Output		Outlet		Rated		Maximum		Dimension		Weight Kg
	HP	W	mm	inch	Head(M)	Flow(l/m)	Head(M)	Flow(l/m)	L x W x H (mm)		
MT-43(K)(T)	1	750	25*25	1" * 1"	30	65	39	110	384 x 170 x 210	10	
MT-44(K)(T)	1 1/3	1000	25*25	1" * 1"	40	65	53	110	408 x 170 x 210	10	
MT-45(K)(T)	2	1500	25*25	1" * 1"	50	65	66	110	470 x 170 x 210	10	
MT-46(K)(T)	2	1500	25*25	1" * 1"	60	65	79	110	495 x 170 x 210	11	
MT-82(K)(T)	1 1/2	1100	40*32	1-1/2" * 1-1/4"	18	133	21	300	435 x 152 x 225	20	
MT-83(K)(T)	1 1/2	1100	40*32	1-1/2" * 1-1/4"	28	133	32	300	474 x 152 x 225	21	
MT-84(K)(T)	2	1500	40*32	1-1/2" * 1-1/4"	37	133	42	300	513 x 152 x 225	22	
MT-85(K)(T)	3	2200	40*32	1-1/2" * 1-1/4"	46	133	53	300	552 x 152 x 225	24	

Remark: Model ends with "K" means with stainless steel impellers. "T" means three phase motor.