



CATALOGO - CATALOGUE

50 Hz - 2014



ELETTROPOMPE CENTRIFUGHE NORMALIZZATE STANDARDIZED CENTRIFUGAL PUMPS

F



Elettropompe centrifughe monoblocco - (EN 733)

Standardized centrifugal pumps - (EN 733)

MODEL (n= 2900 1/min)		P2		Q	H
~	3~	kW	HP	l/min	m
Fm 32/160C	F 32/160C	1.5	2	100 ÷ 350	24 ÷ 14
Fm 32/160B	F 32/160B	2.2	3	100 ÷ 400	30 ÷ 17
-	F 32/160A	3	4	100 ÷ 450	37 ÷ 24
-	F 32/200C	4	5.5	100 ÷ 450	44 ÷ 31.5
-	F 32/200B	5.5	7.5	100 ÷ 500	51 ÷ 36
-	F 32/200A	7.5	10	100 ÷ 500	57 ÷ 44
-	F 32/200BH	3	4	100 ÷ 300	45 ÷ 37
-	F 32/200AH	4	5.5	100 ÷ 320	55 ÷ 44
Fm 40/160C	F 40/160C	2.2	3	100 ÷ 600	27 ÷ 14
-	F 40/160B	3	4	100 ÷ 600	32 ÷ 20
-	F 40/160A	4	5.5	100 ÷ 700	38 ÷ 20
-	F 40/200B	5.5	7.5	100 ÷ 700	47 ÷ 28
-	F 40/200A	7.5	10	100 ÷ 700	55 ÷ 41
-	F 40/250C	9.2	12.5	100 ÷ 700	64 ÷ 47
-	F 40/250B	11	15	100 ÷ 700	71 ÷ 55
-	F 40/250A	15	20	100 ÷ 700	88 ÷ 72
Fm 50/125C	F 50/125C	2.2	3	300 ÷ 1200	17.5 ÷ 6
-	F 50/125B	3	4	300 ÷ 1200	20.7 ÷ 9
-	F 50/125A	4	5.5	300 ÷ 1200	23.5 ÷ 13
-	F 50/160C	4	5.5	300 ÷ 1000	27 ÷ 16
-	F 50/160B	5.5	7.5	300 ÷ 1100	32 ÷ 21
-	F 50/160A	7.5	10	300 ÷ 1100	37 ÷ 27
-	F 50/200C	11	15	400 ÷ 1700	44 ÷ 30
-	F 50/200B	15	20	400 ÷ 1700	52 ÷ 38
-	F 50/200A	18.5	25	400 ÷ 1800	61 ÷ 45
-	F 50/200AR	22	30	400 ÷ 1800	69 ÷ 53
-	F 50/250D	9.2	12.5	300 ÷ 900	51 ÷ 32
-	F 50/250C	11	15	300 ÷ 900	59 ÷ 42
-	F 50/250B	15	20	300 ÷ 1000	72 ÷ 59
-	F 50/250A	18.5	25	300 ÷ 1000	85 ÷ 73
-	F 50/250AR	22	30	300 ÷ 1000	95 ÷ 83
-	F 65/125C	4	5.5	600 ÷ 1800	16 ÷ 11
-	F 65/125B	5.5	7.5	600 ÷ 2000	18 ÷ 13
-	F 65/125A	7.5	10	600 ÷ 2200	23 ÷ 18
-	F 65/160C	9.2	12.5	600 ÷ 2200	32 ÷ 22
-	F 65/160B	11	15	600 ÷ 2400	36.5 ÷ 23
-	F 65/160A	15	20	600 ÷ 2400	40.5 ÷ 28
-	F 65/200B	15	20	200 ÷ 2400	44 ÷ 30.5
-	F 65/200A	18.5	25	200 ÷ 2600	50 ÷ 36.5
-	F 65/200AR	22	30	200 ÷ 2600	57 ÷ 42
-	F 65/250C	30	40	400 ÷ 2350	76 ÷ 53
-	F 65/250B	37	50	400 ÷ 2500	87 ÷ 62
-	F 65/250A	45	60	400 ÷ 2600	94.5 ÷ 68

ELETTROPOMPE CENTRIFUGHE NORMALIZZATE STANDARDIZED CENTRIFUGAL PUMPS

F



Elettropompe centrifughe monoblocco - (EN 733) Standardized centrifugal pumps - (EN 733)

MODEL (n= 2900 1/min) 3~	P2		Q l/min	H m
	kW	HP		
F 80/160D	11	15	500 ÷ 4000	25 ÷ 10
F 80/160C	15	20	500 ÷ 4000	30 ÷ 15
F 80/160B	18.5	25	500 ÷ 4000	35 ÷ 20
F 80/160A	22	30	500 ÷ 4000	40 ÷ 25
F 80/200B	30	40	500 ÷ 3650	56 ÷ 34.5
F 80/200A	37	50	500 ÷ 3900	62 ÷ 40
F 80/250B	45	60	600 ÷ 3600	77 ÷ 54
F 80/250A	55	75	600 ÷ 3900	88.5 ÷ 60
F 100/160C	15	20	1000 ÷ 5000	28 ÷ 12
F 100/160B	18.5	25	1000 ÷ 5500	32 ÷ 13
F 100/160A	22	30	1000 ÷ 6000	35 ÷ 15
F 100/200C	30	40	833 ÷ 4650	51 ÷ 28
F 100/200B	37	50	833 ÷ 4900	57 ÷ 33
F 100/200A	45	60	833 ÷ 5250	63 ÷ 38
F 100/250B	55	75	800 ÷ 5150	75 ÷ 48
F 100/250A	75	100	800 ÷ 5750	89 ÷ 58

F- INOX



Elettropompe monoblocco in acciaio inox - (EN 733) Stainless steel standardised pumps - (EN 733)

MODEL (n= 2900 1/min) 3~	P2		Q l/min	H m
	kW	HP		
F 50/160C - I	4	5.5	300 ÷ 1000	27 ÷ 16
F 50/160B - I	5.5	7.5	300 ÷ 1100	32 ÷ 21
F 50/160A - I	7.5	10	300 ÷ 1100	37 ÷ 27
F 65/125C - I	4	5.5	600 ÷ 1800	16 ÷ 11
F 65/125B - I	5.5	7.5	600 ÷ 2000	18 ÷ 13
F 65/125A - I	7.5	10	600 ÷ 2200	23 ÷ 18