



**CATALOGO - CATALOGUE**  
**50 Hz - 2014**



**PK**



## Elettropompe con girante periferica - Peripheral pumps

MODEL		P2		Q	H
~	3~	kW	HP	l/min	m
PKm 60°	PK 60°	0.37	0.50	5 ÷ 40	38 ÷ 5
PKm 60°-MD	PK 60°-MD	0.37	0.50	5 ÷ 55	22 ÷ 3
PKm 65	PK 65	0.50	0.70	5 ÷ 50	50 ÷ 8
PKm 70	PK 70	0.60	0.85	5 ÷ 50	62 ÷ 18
PKm 80	PK 80	0.75	1	5 ÷ 50	66 ÷ 22
PKm 90	PK 90	0.75	1	5 ÷ 40	82 ÷ 5
PKm 100	PK 100	1.1	1.5	5 ÷ 70	80 ÷ 15
PKm 200	PK 200	1.5	2	5 ÷ 80	86 ÷ 10
—	PK 300	2.2	3	5 ÷ 90	95 ÷ 10

**PKS**



## Elettropompe autoadescenti con girante periferica

### Self-priming peripheral pumps

MODEL		P2		Q	H
~	3~	kW	HP	l/min	m
PKSm 60	PKS 60	0.37	0.50	5 ÷ 40	38 ÷ 5
PKSm 65	PKS 65	0.50	0.70	5 ÷ 50	50 ÷ 8
PKSm 70	PKS 70	0.60	0.85	5 ÷ 50	62 ÷ 18
PKSm 80	PKS 80	0.75	1	5 ÷ 50	66 ÷ 22

**PQ**



## Elettropompe con girante periferica - Peripheral pumps

MODEL	P2		Q	H
3~	kW	HP	l/min	m
PQ 3000	2.2	3	10 ÷ 50	160 ÷ 50